

**NEW**

**GRAPHTEC**

# 平台式切割機/繪圖機

## FC4500 Series

**噴沙標誌模板**

A1-size FC45100-60



**電腦輔助設計鞋版**



A2-size FC4500-50

**印刷模版**



**輪廓切割/盒型刀模/貼紙切割**



FC4500 系列		
Parameter	FC4500-50	FC4510-60
機構方式	平台式	
驅動方式	數位伺服系統	
有效切割範圍	23.2 in. x 16.9 in. (590 mm. x 430 mm.)	33.9 in. x 23.6 in. (860 mm. x 600 mm.)
最大裝載寬度	19.7 in. (500 mm.)	
材料固定方式	Electrostatic adhesion sheet	Adhesive mat or adhesive sheet
最高切割速度	29.5 in./sec (750 mm./sec)	
切割速度(13段)	1 to 10, 15, 20, 25, 30, 35, 40, 45, 50, 55, 60, 65 cm/sec	
切割壓力	10 to 600 g	
機構解析度	.0002 in. (0.005 mm.)	
程式語言解析度	GP-GL™: .004 in., .002 in., .001 in., .0004 in.; HP-GL®: .001 in. (GP-GL™: 0.1 mm., 0.05 mm., 0.025 mm., 0.01 mm.; HP-GL®: 0.025 mm.)	
重覆精度	Within .0039 in. *1 (0.1 mm.)	
尺寸精度	Within ±0.2% of the distance moved or ±0.1 mm. - whichever is greater *1	
垂直度	Within 0.012 in./16.9 in. (0.3 mm./430 mm.)	Within 0.016 in./24.0 in. (0.4 mm./610 mm.)
電眼對位精度	Within 0.012 in. *2 (0.3 mm.)	0.008 in. (0.2 mm.)
切割刀及筆的數量	Two (one cutter and one pen)	One (creasing tool)
切割刀及筆的種類	Cutter blade: supersteel Pens: Water-based ballpoint, oil-based ballpoint	
介面	RS-232C serial and Centronics parallel (auto interface recognition)	
緩充區容量	2 MB	
程式語言格式	GP-GL™ and HP-GL® emulation (control panel selectable)	
LCD 顯示	20 characters x 2 rows	
電源	100 to 120 VAC, 50/60 Hz; 220 to 240 VAC, 50 Hz (please specify when ordering)	
消耗功率	Within 120 VA	
操作環境	+50° to +95°C, 35% to 75% RH (non-condensing)	
外觀尺寸 (W x D x H)	33.8 in. x 30.7 in. x 7.9 in. (857 mm x 780 mm x 200 mm)	46 in. x 37.8 in. x 7.9 in. (1172 mm x 960 mm x 200 mm)
重量	42 lbs. *6 (19 kg.)	59.5 lbs. *6 (27 kg.)

<http://www.vancolor.com.tw>

 **汎彩有限公司**

**VanColor Tech CO., LTD.**

**320 中壢市民族路272號**

**Tel:(03)493-6095 Fax:(03)493-6609**

### 服務項目

系統規劃 整合 買賣 維修服務

數位影像/電腦週邊/系統整合/維修服務

EPSON大圖展示中心/Mimaki、Roland大型噴畫機/割字機